_ALLRECO

CERON TYPE 308

TECHNICAL DATA



| Weight | 38.500 kg |
|-------------------------|--|
| Length (Basic machine) | 7.450 mm |
| Width (Basic machine) | 2.900 mm |
| Height (Basic machine) | 3.190 mm |
| Motor type | Three-phase motor with frequency converter |
| Rated power | 315 / 450 kW |
| Infeed width (minimal) | 3.620 mm |
| Infeed height (minimal) | 2.890 mm |
| Shaft | |
| Length | 3.060 mm |
| Diameter | 800 / 1.000 mm |
| Rotational speed | 18-36 rpm, 14-29 rpm, 13-26 rpm (depending on equipment) |
| Number of shaft teeth | Depending on equipment |

Freely selectable shredding system in sizes S, M, L and XL. Conversion to other tooth sizes possible.

The technical data are approximate and depends on the machine equipment (subject to change without notice).











All advantages at a glance

- Powerful and impurity resistant
- · Maximum throughput for difficult shredding
- Highly efficient, speed adjustable drive
- Robust solid steel construction
- Coarse shredding (prevention of fines)
- User-friendly access and low maintenance
- Low operating costs
- Low dust and noise emission
- Automatic detection of contaminants and discharge
- · Quick-change system for wear parts